ZERO-1 JAMMA

FEATURING

JAMMA CONNECTORS intel_® X SERIES PROCESSOR




SIMPLY PLUG IN & TAKE FLIGHT

Intel® UHD Graphics 32GB Memory x6425E Quad-Core 64-bit Processors









ZERO-1 AMMAL

Zero-1 JAMMA features universal JAMMA connectors that allows hassle-free board swtich whilst delivering seamless player experience. Simply plug in and connect to the ultimate gaming world.



| | Processing Unit | Intel Atom® Embedded X Series Processor x6425E Quad core 64-bit processors | Main Memory | Dual channels DDR4-3200 non- ECC support Two DDR4 SODIMM sockets |
|--|-----------------|---|--------------------------|--|
| | | Support up to 4/4 threads | | Up to 32GB memory |
| | | 2.0GHz processor base frequency | I/O Port | 4 x USB3.1 and 8 x USB2.0 port |
| | | 1.5MB L2 Cache | | 2 x Gigabit Ethernet port |
| | | Max. 12W TDP | | 2 x RS232/SAS |
| | Integrated GPU | Intel® UHD graphics engine | | 1 x ccTalk/TTL |
| | | Up to three independent DisplayPort v1.4 channels | | 1 x RS232/422/485 |
| | | Up to 4096x2160 @60Hz Resolution | NVRAM | 4MB battery backup SRAM |
| | | Hardware accelerated UHD video encoder/decoder | | 5-year battery life |
| | JAMMA Interface | One 2 x 36 JAMMA slot | Security | 7 x Intrusion input |
| | | One 2 x 10 JAMMA slot | | TPM 2.0 |
| | Storage | 1 x CFast socket | | Watch Dog timer |
| | | 1 x M.2, supports M key type 2242/2280 M.2 PCI Express | Digital Input/ Output | 24 x Opto-isolated Digital Input |
| | | 1 x SATA3 for 2.5" HDD/SSD/ SATADOM | | 24 x Darlington Digital Output |
| | Audio | R/L audio output | Hardware Meter | 8 x Meter Interface |
| | | Line in/out and MIC in | Power Input | 12VDC input |